

Article Number: 181-13011

Description: Slotted Cable and Wiring Duct, 1" x 3", Adhesive, PVC,

HellermannTyton

White, 30ft/box

Base Data		
	Local Order Number	181-13011
	Туре	SLA1X3
	Color	White (WH)
	Features and Benefits	 Strong fingers prevent unwanted breaking. Fingers are easily deflected outward, allowing ready positioning of the wires within the slotted wall duct. Restricted opening prevents unintended removal of wires and permits any individual wire to be traced without disconnection.
	Quantity Per	box
	Product Description	Pro-Duct slotted wall wiring duct features break-away fingers which provide additional access for wire leads. Each section of the duct is provided with two score lines. The upper score line is used to break away fingers when a wider opening is required. The lower score line allows the sidewall to be smoothly cut for joints and "T's".
	Technical Description	Adhesive
	Short Description	Slotted Cable and Wiring Duct, 1" x 3", Adhesive, PVC, White, 30ft/box
Product Dimensions		
	Length L (Imperial)	6.0ft
	Length L (Metric)	1.83m
	Width W (Imperial)	1.0"
	Width W (Metric)	25.4mm
	Width W2 (Imperial)	1.0"
	Width W2 (Metric)	25.4mm
	Width W3 (Imperial)	0.4"
	Width W3 (Metric)	10.2mm
	Width W4 (imperial)	1.0"
	Width W4 (metric)	25.4mm
	Width W5 (imperial)	2.6"
	Width W5 (metric)	66.0mm

generated on: 4/28/2017

181-13011



Product Dimensions Height H (Imperial) 3.07" Height H (Metric) 77.9mm Mounting Hole Centers (Imperial) 4.0* Material and Specifications Pecifications Material Polyvinylchloride (PVC) Material Shortcut PVC Flammability self-extinguishing Operating Temperature +122°F (+50°C) ROHS Compliant Yes Certification/Specification UL UL Recognized (US) Yes Logistic and Packaging Package Quantity (Imperial) 30.0ft Package Quantity (Metric) 9.1m Customs Number(Schedule B) 3925900000			
Height H (Metric) //-9mm Mounting Hole Centers (Imperial) 4.0" Material and Specifications Material Polyvinylchloride (PVC) Material Shortcut PVC Flammability self-extinguishing Operating Temperature +122°F (+50°C) ROHS Compliant Yes Certification/Specification UL UL Recognized (US) Yes Logistic and Packaging Package Quantity (Imperial) 30.0ft Package Quantity (Metric) 9.1m		Height H (Imperial)	3.07"
Material and Specifications Material Polyvinylchloride (PVC) Material Shortcut PVC Flammability self-extinguishing Operating Temperature +122°F (+50°C) ROHS Compliant Yes Certification/Specification UL UL Recognized (US) Yes Logistic and Packaging Package Quantity (Imperial) 30.0ft Package Quantity (Metric) 9.1m		Height H (Metric)	77.9mm
Material Polyvinylchloride (PVC) Material Shortcut PVC Flammability self-extinguishing Operating Temperature +122°F (+50°C) ROHS Compliant Yes Certification/Specification UL UL Recognized (US) Yes Logistic and Packaging Package Quantity (Imperial) 30.0ft Package Quantity (Metric) 9.1m		Mounting Hole Centers (Imperial)	4.0"
Material Shortcut PVC Flammability self-extinguishing Operating Temperature +122°F (+50°C) ROHS Compliant Yes Certification/Specification UL UL Recognized (US) Yes Logistic and Packaging Package Quantity (Imperial) 30.0ft Package Quantity (Metric) 9.1m			
Flammability self-extinguishing Operating Temperature +122°F (+50°C) ROHS Compliant Yes Certification/Specification UL UL Recognized (US) Yes Logistic and Packaging Package Quantity (Imperial) 30.0ft Package Quantity (Metric) 9.1m		Material	Polyvinylchloride (PVC)
Operating Temperature +122°F (+50°C) ROHS Compliant Yes Certification/Specification UL UL Recognized (US) Yes Logistic and Packaging Package Quantity (Imperial) 30.0ft Package Quantity (Metric) 9.1m		Material Shortcut	PVC
ROHS Compliant Certification/Specification UL UL Recognized (US) Yes Logistic and Packaging Package Quantity (Imperial) Package Quantity (Metric) 9.1m		Flammability	self-extinguishing
Certification/Specification UL UL Recognized (US) Logistic and Packaging Package Quantity (Imperial) Package Quantity (Metric) 9.1m		Operating Temperature	+122°F (+50°C)
Logistic and Packaging Package Quantity (Imperial) Package Quantity (Metric) 9.1m		ROHS Compliant	Yes
Logistic and Packaging Package Quantity (Imperial) 30.0ft Package Quantity (Metric) 9.1m		Certification/Specification	UL
Packaging Package Quantity (Imperial) 30.0ft Package Quantity (Metric) 9.1m		UL Recognized (US)	Yes
Package Quantity (Metric) 9.1m			
		Package Quantity (Imperial)	30.0ft
Customs Number(Schedule B) 3925900000		Package Quantity (Metric)	9.1m
		Customs Number(Schedule B)	3925900000

generated on: 4/28/2017