

## Datasheet for part number KJL6T17B99PN

Our Catalog Part Number: KJL6T17B99PN

Our Global Manufacturing Part Number: 111079-0087

Brand: Cannon Product Category: Circular Product Line: 38999 Series I, II, and III Series: KJ

| Product Datasheet                 |   |
|-----------------------------------|---|
| SERIES                            | MIL - DTL - 38999 Series I  |
| STYLE                             | Straight plug   |
| CLASS                             | Environment resistant (without rear accessory)                                |
| SHELL SIZE                        | 17  |
| SHELL MATERIAL                    | Corrosion resistant shells of aluminum alloy                                  |
| INSULATOR MATERIAL                | High grade plastic  |
| GROMMET AND SEAL MATERIAL         | Silicone base elastomer   |
| PLATING                           | Olive drab cadmium over electroless nickel plate                              |
| ARRANGEMENT                       | 17-99   |
| NUMBER OF CONTACTS                | 21 contacts size 20 and 2 contacts size 16                                    |
| GENDER                            | Pin   |
| CONTACT TYPE                      | Rear release crimp snap-in contacts   |
| CONTACT MATERIAL                  | Copper Alloy, gold plate  |
| POLARIZATION                      | 95°   |
| LOW PROFILE / LIGHT WEIGHT        | no  |
| SCOOP PROOF                       | yes   |
| COUPLING SYSTEM                   | Bayonet   |
| ELECTROLYTIC EROSION              | no  |
| DURABILITY (CYCLES)               | 500   |
| HIGH IMPACT SHOCK                 | yes   |
| EXTERNAL BENDING MOMENT (Size 25) | 650 in/lbs  |
| RANDOM VIBRATION "J"              | Ambient   |
| SINE VIBRATION                    | 30 G, Ambient   |
| SAND, DUST, ICE                   | yes   |
| TEMPERATURE RANGE                 | 65°C (85°F) to + 175°C (+347°F)   |
| CORROSION RESISTANT               | 500 hours   |
| TEST SERVICE RATING (MATED)       | Sea Level = 1800<br>50000 ft. = 1000<br>70000 ft. = 1000<br>100000 ft. = 1000 |
| TEST SERVICE RATING (UNMATED)     | Sea Level = 1800<br>50000 ft. = 600<br>70000 ft. = 400<br>100000 ft. = 200    |
| OPERATING VOLTAGE                 | Vrms = 600<br>Vdc = 850   |